



P.K.:	0+00.00	0+44.00	0+50.00	1+00.00	1+50.00	2+00.00	2+50.00	3+00.00	3+50.00	4+00.00	4+50.00	5+00.00	5+50.00	6+00.00	6+50.00	7+00.00
COTAS-TERRENO:	65.28	65.27	65.27	65.27	65.27	65.27	65.27	65.27	65.27	65.27	65.27	65.27	65.27	65.27	65.27	65.27
COTAS-RASANTE: <i>Generatriz inferior Tubería</i>	62.11	61.94	61.76	61.59	61.45	61.27	61.03	60.74	60.41	60.04	59.63	59.18	58.69	58.16	57.59	56.99
COTA-ROJA:	3.16	3.43	3.57	3.81	4.49	5.34	6.27	7.24	8.24	9.24	10.24	11.24	12.24	13.24	14.24	15.24
DISTANCIA-ORIGEN:	0.00	10.00	20.00	30.00	40.00	50.00	60.00	70.00	80.00	90.00	100.00	110.00	120.00	130.00	140.00	150.00
DISTANCIA-PARCIAL:	-10.00	-10.00	-10.00	-10.00	-10.00	-10.00	-10.00	-10.00	-10.00	-10.00	-10.00	-10.00	-10.00	-10.00	-10.00	-10.00
PENDIENTE:	-1.72%	14.21%	7.11%	6.21%	4.61%	5.06%	5.86%	11.47%	7.99%	8.61%	6.26%	7.7				
TUBERIA:	TUBERÍA EXISTENTE Acero ø1.700mm.	TUBERÍA EXISTENTE Hormigón armado con camisa de chapa ø1.700mm. / P.S. 10 Atm.	TUBERÍA EXISTENTE Hormigón armado con camisa de chapa ø1.700mm. / P.S. 75 Atm.													